

A1
604 alternative embodiments, the voltage is tested between approximately every two to one hundred sixty four seconds.

IN THE CLAIMS

A2 Sub B1 1. (once amended) A method for protecting an electrical device, said method comprising the steps of:

monitoring a line rms voltage to detect a high voltage condition such that the rms voltage is above a predetermined voltage range;

monitoring the line rms voltage to detect a low voltage condition such that the rms voltage is below the predetermined range; and

electrically isolating the electrical device such that the electrical device does not receive electricity when at least one of a high voltage condition and a low voltage condition is detected.

Sub D1 2. (once amended) A method according to Claim 1 further comprising the step of monitoring the line rms voltage after electrically isolating the electrical device.

3. (once amended) A method according to Claim 2 further comprising the step of restoring power to the electrical device when the line rms voltage is within the predetermined voltage range.

4. (once amended) A method according to Claim 1 further comprising the step of providing a visual indication that the line rms voltage is being monitored.

Sub D1 A3 9. (once amended) A method according to Claim 1 wherein said step of monitoring the line rms voltage comprises the step of providing a visual indication when the line voltage is being tested.

Sub B3 10. (once amended) A circuit for protecting an electrical device, said circuit configured to:

monitor a line rms voltage to detect a rms voltage above a predetermined voltage range;

B3
art 1
A3
641
monitor the line rms voltage to detect a rms voltage below the predetermined range;

and

electrically isolate the electrical device such that the electrical device does not receive electricity when at least one of a rms voltage above the predetermined voltage range and a rms voltage below the predetermined range is detected.

Sub
D1
11. (once amended) A circuit according to Claim 10 further configured to monitor the line rms voltage after electrically isolating the electrical device.

12. (once amended) A circuit according to Claim 11 further configured to restore power to the electrical device when the line rms voltage is within the predetermined voltage range.

Sub
D1
A4
14. (once amended) A circuit according to Claim 10 further configured to provide a visual indication when a rms voltage below the predetermined voltage range is detected.

15. (once amended) A circuit according to Claim 10 further configured to:
provide a visual indication when a rms voltage below the predetermined voltage range is detected; and

provide a visual indication when a rms voltage above the predetermined voltage range is detected.

16. (once amended) A circuit according to Claim 12 further configured to provide a visual indication when a rms voltage below the predetermined voltage range is detected.

17. (once amended) A circuit according to Claim 12 further configured to:
provide a visual indication when a rms voltage below the predetermined voltage range is detected; and

provide a visual indication when a rms voltage above the predetermined voltage range is detected.

Sub
B4
A5
20. (once amended) A circuit for protecting an electrical device, said circuit configured to: